



## Enterprise SSDs

Leveraging state-of-the-art BiCS FLASH™ 3D flash memory with in-house designed controllers and firmware, KIOXIA enterprise SSDs optimize high performance, endurance and reliability to run mission critical applications in enterprise data center environments. To meet the demands of highly transactional and high-bandwidth workloads, these SSDs feature high levels of performance and data protection with power-loss-protection (PLP)<sup>\*1</sup>. KIOXIA enterprise SSDs offer a range of security options<sup>\*2</sup> designed for business critical data storage.



Product image may differ from the actual product.



### KIOXIA FL6 Series

The FL6 series is a dual-port PCIe® 4.0 / NVMe™ SSD utilizing low latency, high endurance KIOXIA XL-FLASH Storage Class Memory (SCM). It provides fast system response for latency-sensitive applications, such as server caching, write logging, and read / write cache for tiered storage in enterprises and hyperscale data centers.

Model Number	DWPD <sup>*3</sup>	Interface	Form Factor	User Capacity (GB) <sup>*4</sup>	Performance (up to)				Typical Power Consumption (W)	Operating Temperature (°C) <sup>*9</sup>	Dimensions T / W / L (mm) <sup>*11</sup>
					Sequential (128 KiB) <sup>*5 *6 *7</sup> (MB/s)		Random (4 KiB) <sup>*5 *6 *7 *8</sup> (KIOPS)				
					Read	Write	Read	Write			
<b>KFL61HUL3T20</b>	60	PCIe® Gen4 single x4, dual x2	2.5-inch	3,200	6,200	6,200	1,500	400	19	0 to 70	15.0 / 69.85 / 100.45
<b>KFL61HUL1T60</b>				1,600			380	16			
<b>KFL61HUL800G</b>				800			360	14			

## KIOXIA CM7 Series

Based on BiCS FLASH™ generation 5, the CM7 Series of dual-port PCIe® 5.0/ NVMe™ SSDs is available in 2.5-inch and E3.S form factor with capacities up to 30.72 TB. These SSDs feature Power Loss Protection (PLP) and offer a range of security/encryption options\*2.

Model Number	DWPD	Interface	Form Factor	User Capacity (GB)	Performance (up to)				Typical Power Consumption (W)	Operating Temperature (°C)	Dimensions T / W / L (mm)							
					Sequential (128 KiB) *5 *6 *7		Random (4 KiB) *5 *6 *7 *8											
					Read	Write	Read	Write										
KCMY1VUG12T8	3	PCIe® Gen5 single x4, dual x2	2.5-inch	12,800	14,000	7,000	2,400	550	25	0 to 73	15.0 / 69.85 / 100.45							
KCMY1VUG6T40				6,400								2,450	550					
KCMY1VUG3T20				3,200										2,700	600			
KCMY1VUG1T60				1,600												2,000	310	
KCM71VJE12T8	3	PCIe® Gen5 single x4, dual x2	E3.S	12,800	14,000	5,300	2,000	470	25	0 to 73	7.5 / 76.0 / 112.75							
KCM71VJE6T40				6,400								2,450	550					
KCM71VJE3T20				3,200										2,700	600			
KCM71VJE1T60				1,600												2,000	310	
KCMY1RUG30T7	1	PCIe® Gen5 single x4, dual x2	2.5-inch	30,720	14,000	4,900	1,600	150	25	0 to 72	15.0 / 69.85 / 100.45							
KCMY1RUG15T3				15,360								7,000	2,400	300				
KCMY1RUG7T68				7,680											2,450	300		
KCMY1RUG3T84				3,840													2,700	310
KCMY1RUG1T92				1,920														
KCM71RJE15T3	1	PCIe® Gen5 single x4, dual x2	E3.S	15,360	14,000	5,300	2,000	260	25	0 to 73	7.5 / 76.0 / 112.75							
KCM71RJE7T68				7,680								6,750	2,450	300				
KCM71RJE3T84				3,840											2,700	310		
KCM71RJE1T92				1,920													3,500	2,000

## KIOXIA PM7 Series

Based on BiCS FLASH™ generation 5, the PM7 Series of dual-port 24G SAS SSDs is available in a 2.5-inch form factor with capacities up to 30.72 TB. These SSDs feature Power Loss Protection (PLP) and offer a range of security/encryption options\*2.

Model Number	DWPD	Interface	Form Factor	User Capacity (GB)	Performance (up to)				Power Consumption Mode (W)	Operating Temperature (°C)	Dimensions T / W / L (mm)						
					Sequential (128 KiB) *5 *6 *7		Random (4 KiB) *5 *6 *7 *8										
					Read	Write	Read	Write									
KPM71VUG12T8	3	SAS-4 Narrow Single Narrow Dual	2.5-inch	12,800	4,200	4,100	720	330	9 / 12 / 14 / 18	0 to 70	15.0 / 69.85 / 100.45						
KPM71VUG6T40				6,400								3,650	340				
KPM71VUG3T20				3,200										3,400	320		
KPM71VUG1T60				1,600												3,400	320
KPM71RUG30T7	1	SAS-4 Narrow Single Narrow Dual	2.5-inch	30,720	4,200	3,200	720	80	9 / 12 / 14 / 18	0 to 70	15.0 / 69.85 / 100.45						
KPM71RUG15T3				15,360								4,100	175				
KPM71RUG7T68				7,680										3,650	155		
KPM71RUG3T84				3,840												3,400	155
KPM71RUG1T92				1,920													

\*1 : PLP (Power Loss Protection): PLP allows to record data in buffer memory to flash memory, utilizing back up power of solid capacitor in case of sudden supply shut down.

\*2 : Optional security features

- Drive models with different security options have different model numbers.
- FL6, CM7 and PM7 Series security options: The Sanitize Instant Erase (SIE), Self-Encrypting Drive (SED), FIPS (Federal Information Processing Standards) SED optional models are available.
- FL6 and CM7 Series: SED optional models support TCG Opal and Ruby SSCs. It has a few unsupported TCG Opal features.
- PM7 Series: SED optional models support TCG Enterprise SSC.
- SIE optional models support Crypto Erase, which is a standardized feature defined by the technical committees (T10) of INCITS (the InterNational Committee for Information Technology Standards).
- FIPS SED optional models of FL6 and PM7 utilize security modules designed to comply with FIPS 140-2 and FIPS 140-3, which define security requirements for cryptographic module by NIST (National Institute of Standards and Technology). FIPS SED optional models of CM7 utilize a security module designed to comply with FIPS 140-3.
- For more details and the latest validation status of each drive, please make inquiries through "Contact us" in each region's website, <https://www.kioxia.com/>.
- Optional security feature compliant models are not available in all countries due to export control and local regulations.

\*3 : DWPD: Drive Writes Per Day. One full drive write per day means the drive can be written and re-written to full capacity once a day every day for the specified lifetime. Actual results may vary due to system configuration, usage and other factors.

\*4 : Definition of capacity: 1 terabyte (1 TB) = 1,000 gigabytes (GB), 1 GB = 1,000,000,000 (10<sup>9</sup>) bytes

\*5 : A kibibyte (KiB) means 2<sup>10</sup>, or 1,024 bytes.

\*6 : The performance of the CM7 Series is based on single-port mode (single x4). The performance specifications of the PM7 Series is based on testing in dual-port mode, running at 18 W of power.

\*7 : Read and write speeds may vary depending on various factors such as host devices, software (drivers, OS etc.), and read/write conditions.

\*8 : IOPS: Input Output Per Second (or the number of I/O operations per second)

\*9 : Case surface temperature

\*10 : Composite temperature reported by SMART.

\*11 : Dimensions represent the nominal values.

Customers must refer to and comply with the latest versions of all relevant KIOXIA information, including without limitation, this document, the specifications, the data sheets and application notes for Product and the precautions and conditions set forth in the KIOXIA Reliability Handbook and the instructions for the application with which the Product will be used with or for.

All information provided in this catalog is subject to change without any prior notice. For the latest and detail specification, please send an inquiry through "Contact us" in each region's website, <https://www.kioxia.com/>.

The following trademarks, service and/or company names – PCIe, PCI-SIG, NVMe, NVM Express, Inc., MultiLink SAS, SCSI Trade Association – are not applied, registered, created and/or owned by KIOXIA Europe GmbH or by affiliated KIOXIA group companies. However, they may be applied, registered, created and/or owned by third parties in various jurisdictions and therefore protected against unauthorized use.