



ASKEY-RTM7230T

Tri-Band Wi-Fi 7 Router

RTM7230T, Tri-band Wi-Fi 7 router provides an unprecedented performance, proven reliability, great scalability and whole-home coverage, perfect for residence applications.

Wi-Fi 7 Technology with Blazing-Fast Speed and Lag-Free Performance

RTM7230T adopts Wi-Fi 7 standard, supporting 4096QAM, 320MHz and MLO technologies. It delivers speeds up to 688Mbps with 2.4GHz, 2882Mbps with 5GHz, and 5764Mbps with 6GHz. Whole new 6GHz band has no interference from other existing wireless signals, achieving super wider spectrum, extreme fast speed, feeless interference and lag-free latency.

EasyMesh for Whole Home Coverage

Easily set up a robust and powerful Wi-Fi network by EasyMesh and enjoy seamless experience in a whole home environment when users move from room to room, keeping their real-time usage without latency.

Dedicated 2.5GbE WAN Port for MultiGig Internet Access

With one 2.5GbE WAN port, RTM7230T extends premium fiber service to subscribers' dwellings. Besides Wi-Fi BE9400 speed, it also offers one 2.5GbE and two 1GbE LAN ports to satisfy high speed requirements of wireless and wireline network for residence applications.

Router | Wi-Fi 7 | Tri-Band

System

- Wireless Standard:
802.11 b/g/n/ac/ax/be 2.4GHz,
data rate 688Mbps
802.11 a/n/ac/ax/be 5GHz,
data rate 2882Mbps
802.11 ax/be 6GHz,
data rate 5764Mbps
- Wireless Feature:
MLO
SSID Broadcast
Auto channel selection
WPS
WPA, WPA2, WPA3 security
Wireless guest network
802.11 k/v/r
EasyMesh with wireless and
wired backhauls
- Firewall:
DMZ
UPnP
MAC/URL/Keyword filter
- Networking:
IPv4/IPv6
NAT
Port forwarding
DHCP/Static IP/PPPoE
DNS
- Management:
Web GUI (HTTP/HTTPS) management
Parental control
TR-069/TR-181
Firmware upgrade through GUI/TR-069
Trouble shooting
Config backup/Restore
Reboot/Factory reset

Hardware

- Chipsets:
MediaTek Filogic platform
- WAN:
1 x 2.5GbE RJ-45 Port
- LAN:
1 x 2.5GbE RJ-45 Port
2 x 1GbE RJ-45 Port
- USB:
1 x USB 3.0 Type A
- LED:
4 x LED (Green/Red) for Power,
LAN, Mesh and Internet
- Button:
Power, Reset and WPS
- Antenna:
2 x 2.4/5GHz dual band antenna
2 x 6GHz single band antenna
1 x 5Hz single band antenna for DFS
- PSU:
12V/2.5A
- Dimension:
80 x 182 x 130 (WxHxD, mm)

Environments

- Operating Environment:
Temperature: 0°C to 40°C
Humidity: 5% to 85% RH
- Storage Environment:
Temperature: -20°C to 70°C
Humidity: 5% to 85% RH
- Certifications:
FCC
UL
WFA
EasyMesh



ASKEY Computer Corporation

10F, NO.119, Jiankang Road
Zhonghe District
New Taipei City 23585
TAIWAN, R.O.C.

TEL. +886-2-2228-7588
FAX. +886-2-3234-9211
www.askey.com.tw
sales@askey.com.tw

Askey is a registered trademark of Askey Computer Corporation
All mentioned brands are trademarks of their respective owners
All specification, features and pictures are subject to change
without notice